

Specifications

Eaton 8MQ2M0412UB046

Catalog Number: 8MQ2M0412UB046

MQuick module, unsealed, with female straight PCB contacts, tin lead plated

General specifications



Product Name	Catalog Number
Eaton Souriau Mquick series rectangular modular small-size push-pull connector	8MQ2M0412UB046
Product Length/Depth	33.2 mm
Product Height	Product Width
14.4 mm	33.2 mm
Product Weight	
3.3 g	

Product specifications

Contact delivery

Loaded

Contact gender

Socket (Female)

Contact plating

Gold on active part, Tin on rear part

Contact type

PCB

Layout

04-12

Shell material

Composite

Mating cycles

500

Operating temperature - max

175 °C

Operating temperature - min

-55 °C

Number Of Contacts

4

Resources

Drawings

c0128mqa.pdf

Product specifications

Contact delivery

Loaded

Contact gender

Socket (Female)

Contact plating

Gold on active part, Tin on rear part

Contact type

PCB

Layout

04-12

Shell material

Composite

Mating cycles

500

Operating temperature - max

175 °C

Operating temperature - min

-55 °C

Number Of Contacts

4

Eaton Corporation plc
Eaton House

30 Pembroke Road
Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia