



 PRODUCT-DETAILS

20 EUCB2USBAC-82-500

Socket insert Safety Shutter with USB AC ivory white - Platform 63



General Information

Extended Product Type	20 EUCB2USBAC-82-500
Product ID	2CKA002011A6303
EAN	4011395329306
Catalog Description	Socket insert Safety Shutter with USB AC ivory white - Platform 63
Long Description	<p>SCHUKO®/USB A&C socket outlet With screwless terminals. For connecting electric loads. For supply and support of mobile devices via USB-cable. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. With 1x USB type A and 1x USB type C outputs. Support of loading protocol on the USB-A connection: Apple MFI with 2.4 A and BC 1.2 with 1.5 A. Support of loading protocol on the USB-C connection: USB-PD till 3 A, Apple MFI till 2.4 A and BC 1.2 with 1.5 A. With electronic short-circuit protection. With electronic overload protection. USB-A port: Max. current 2.4 A. USB-C port: Max. current 3 A* *3 A requires approved charging cables.</p> <p>No data transfer between USB ports. Use dust cover 2098-500 for USB-A port when cleaning the device.</p>

Installation

Instructions and Manuals	2CKA000073B5396 2CKA000073B5397 2CKA000073B5398
Mounting Type	Flush Mounted
Type of Fastening	Mounting with Claw Mounting with Screw

Environmental

Ambient Air Temperature	Operation 5 ... +35 °C
Degree of Protection	IP20

Technical

Function	USB with enhanced contact protection
Number of Poles	2+PE
Number of Phases	1
Number of Outputs	3 USB-A 1
Number of Gangs	1
Connection Type	Plug Clamp
Socket Outlet Type	Protective Contact (SCHUKO)
Terminal Type	Screwless Terminals
Safety Function Option	Safety Shutter

Electrical

Short-Circuit Current Rating (SCCR)	0 kA
Rated Voltage (U_r)	230 V
Secondary Voltage	5 V
Rated Current (I_n)	16 A
Rated Frequency (f)	50 / 60 Hz
Load Type	SCHUKO® socket outlet
Power Loss	0.075 W
Power Supply Type	Integrated

Design

Design Range	Platform 63 future linear solo carat Busch-Dynasty
Design Range Variant	future future linear
Surface Finishing	Untreated Glossy
Material	Thermoplastic
RAL Number	Similar to RAL 1013

Color	ivory white
-------	-------------

Dimensions

Product Net Width	71 mm
Product Net Height	71 mm
Product Net Depth / Length	57.8 mm
Product Net Weight	104 g
Built-In Depth (t ₂)	39.5 mm

Material Compliance

RoHS Information	2CKA200000E7802
RoHS Status	Following EU Directive 2011/65/EU
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240705
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Certificates and Declarations

Declaration of Conformity - CE	2CKA100000E4820
--------------------------------	-----------------

Classifications

ETIM 9	EC000125 - Socket outlet
eClass	V11.0 : 27144042
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

