



PRODUCT-DETAILS

JSTD25P-1

JSTD25P-1 Safety Control Devices



General Information	
Extended Product Type	JSTD25P-1
Product ID	2TLA020007R6500
EAN	7350024465716
Catalog Description	JSTD25P-1 Safety Control Devices
Long Description	JSTD25P-1 mobile 2-hand device 2x Safeball, EVA, male connector M23/9-pol., IP40

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Product Main Type	JSTD25
Product Name	Safety Control Devices
Special Functions	Eden Sensor "EVA"

Popular Downloads	
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Depth / Length	70 mm
Product Net Height	160 mm
Product Net Width	315 mm
Product Net Weight	0.8 kg

Safety Information

Safety Category	4
Performance Level (PL)	Up to e
Safety Integrity Level (SIL)	3
B10d Value	Operations 20 million

Technical

Connection Configuration	M23-9 male
Rated Operational Voltage	10 ... 30 V DC

Environmental

Ambient Air Temperature	Operation -25 ... +50 °C
Degree of Protection	IP40

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	2CMT2022-006499
WEEE B2C / B2B	Business To Business
WEEE Category	6. Small IT and Telecommunication Equipment (No External Dimension More Than 50 cm)

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	294 mm
Package Level 1 Depth / Length	392 mm
Package Level 1 Height	120 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	7350024465716

Classifications

eClass	V11.0 : 27371219
ETIM 7	EC001260 - Two-hand control device
ETIM 8	EC001260 - Two-hand control device
ETIM 9	EC001260 - Two-hand control device

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSTD25

